

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 164 796 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

19.12.2001 Bulletin 2001/51(51) Int Cl.7: **H04N 7/173**(21) Application number: **00401679.6**(22) Date of filing: **14.06.2000**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

Designated Extension States:

AL LT LV MK RO SI(71) Applicant: **Astrium SAS****78140 Velizy-Villacoublay (FR)**(72) Inventor: **Gomez, Etienne****31000 Toulouse (FR)**(74) Representative: **Fort, Jacques****CABINET PLASSERAUD 84, rue d'Amsterdam
75440 Paris Cedex 09 (FR)**(54) **Process and system for video on demand**

(57) For providing video-on-demand (VOD) a set comprising a plurality of N video programs at staggered time intervals is repeatedly transmitting from a VOD server to a network for access by a view box of an user; responsive to a request for access to a selected program by the user, there is selection of that in-progress transmission of the selected program for which a lead-in portion is shortest and storage of the program in a buffer associated with the view box as it is transmitted.

A previously stored beginning portion of the selected program having a time length sufficient to compensate for that time interval is selected, in a memory associated with the view box, and outputting to the view box for display. The in-progress transmission stored in the buffer is continuously spliced to a conclusion of the beginning portion. All different video programs in a same set are transmitted with mutual time shifts equal to a fraction of the staggered interval.




FIG. 3.

Description

[0001] The invention relates to Video-On-Demand (VOD) provided by a server to users provided with a view box via a telecommunication network or a satellite link, possibly through the Internet.

[0002] Serving various programs by broadcasting them repeatedly, each new broadcast beginning when the preceding has ended, does not satisfy users. On the other hand serving the selected video program on a separate channel to each user upon request is expensive and inefficient.

[0003] For satisfying a user's request for a video program without too much delay, an approach known as Near-Video-On-Demand (N-VOD) has been developed, wherein each video program is repeatedly made available at a fixed staggered time interval, thereby reducing the maximum delay to the staggered time interval, which is typically several minutes.

[0004] An improvement strongly reducing the maximum time delay between the user's request and the availability of the video program is known as Hybrid-Video-On-Demand (HVOD). A description of that approach is given in US - A 5 682 597 to which reference may be made. According to that approach, multiple copies of each program are continuously sent on separate channels and again the start of each copy is offset by a staggered time interval. At the user's end, VOD requests which are not synchronous with the beginning of a transmission are initially fulfilled with the start of a specific additional transmission of the beginning portion of the selected video program for that user, while simultaneously maintaining use of the NVOD transmission for that requestor. The in-progress transmission of the selected video program is stored in a buffer associated with the viewbox and spliced to a conclusion of the beginning portion of the video program for output by the viewbox and display.

[0005] That approach requires specific transmission of the beginning portion of the selected video program on request by only one user and still increases the amount of network resources which are required. Network resources can be saved by providing a large size buffer in the viewbox and storing the beginning portion of each of the video programs once for each period during which the programs remain unchanged (once a week for instance). Then there is no need to transmit the beginning portion of a selected program to the respective requestor. The volume of data to be transmitted is reduced and transmission of the beginning portions may take place when the network load is low. A user's request for an in-progress program is initially and immediately fulfilled by reading the beginning portion from the buffer while the remaining portion is stored for later readout after splicing. A buffer allowing simultaneous read -out and writing is necessary, since storage proceeds after splicing.

[0006] A limiting factor in the implementation of that approach is the buffer size. Typically transmissions of all video or multimedia programs on the network start at the same time. For any selected program to be immediately available to a user even in the worst conditions, when the request takes place just before a new transmission of the N programs takes place, the buffer capacity required for storing the beginning portions is little less than N times the staggered time interval. A shorter staggered time interval and conversely a greater number of simultaneous time offset transmissions of a same program require a lesser buffer size but increasingly draw on network resources.

[0007] It is an object of the invention to provide an enhanced VOD system and process using a buffer for storing beginning portions of the available programs which spares network or satellite link resources for a given buffer size.

[0008] For that purpose, there is provided a method of providing video-on-demand (VOD) comprising the steps of:

- repeatedly transmitting a set comprising a plurality of N video programs at staggered time intervals from a VOD server to a network for access by a view box of an user, and
- responsive to a request for access to a selected one of said programs by said user,

selecting that in-progress transmission of the selected program for which a lead-in portion is shortest and storing said program in a buffer associated with the view box as it is transmitted,
 selecting, in a memory associated with the view box, a previously stored beginning portion of said selected program having a time length corresponding to that of said time intervals and outputting said beginning portion to said view box for display, and
 continuously splicing the in-progress transmission stored in the buffer to a conclusion of the beginning portion,

characterized in that all different video programs in a same set are transmitted with time shifts equal to a fraction of the staggered interval.

[0009] An optimal value for all time shifts is a fraction $1/N$ of the staggered time interval (time period between two transmissions of a same video program) and provides the greater resource saving for a given buffer size and a given number of programs.

[0010] Preferably transmitting the beginning portion of each specific program into all view boxes connected to the server takes place during the last period of low network load prior to availability of said program from the server and involves erasing the preceding portions.

[0011] There is also provided a video on demand system enabling to carry out the above defined process having :

- at a head end of the network, a server for repeatedly transmitting a set comprising a plurality of N video programs at staggered time intervals (δ) to a network for access by a view box of an user, and
- 5 - at each of user's ends, a viewbox unit having a bidirectional connection with said server, each said endbox comprising :
- a buffer for simultaneous writing in of a program transmitted on the network by said server and read out of said program with a time difference between writing in and read out of a same portion,
- 10 - memory means for storing beginning portions of predetermined duration of a plurality of programs adapted to be received and displayed by said view box unit,
- user operated means for selectively tuning said view box unit for reception of a program repeatedly originating from said server as successive transmissions at time intervals on different channels, and storing that transmission of said program which began most recently as it proceeds,
- 15 - means for reading out the beginning portion of the program which has been selected from the memory means , and
- switching means for splicing the selected beginning portion with the following portion of the same program for display when said following portion becomes available from the buffer,

characterized in that said server is arranged for transmitting all different video programs in a same set with time shifts equal to a fraction of the staggered interval.

[0012] The above and additional features will appear from the following description of particular embodiments of the invention, given by way of examples only. The description refers to the accompanying drawings, wherein :

Fig. 1 is a timing diagram for illustrating the main feature of Hybrid Video On Demand ;

Fig. 2 is a timing diagram illustrating the requirements for a system with storage in a buffer, when all transmissions begin at the same time ;

Fig. 3 is a time diagram illustrating a particular embodiment;

Fig. 4 is a time diagram illustrating another embodiment ; and

Fig. 5 is a simplified block diagram of a server - user system according to the invention.

[0013] For purpose of comparison Fig. 1 indicates the time relationship between successive transmissions of two video programs 1 and 2 by a server in a HVOD system . Successive transmissions of program 1 take place at times separated by intervals δ . A request R by an user, at a time t asynchronous with the beginning of a transmission. The request is initially and immediately fulfilled by a specific transmission of the beginning portion to that single user for immediate display without storage. During that specific transmission, the user's terminal also processes the in-progress transmission and stores it in a buffer of the viewbox. At the end of the beginning portion (earlier than the stored portion), as indicated for example by a flag stored at the server, the specific transmission is stopped and read out of the buffer is initiated. The stored portion is spliced to the end of the beginning portion and at the same time the portion of the program not yet transmitted is stored in the buffer.

[0014] Referring now to Fig. 2, an improved version reducing the need for transmission resources requires a buffer having an increased capacity for continuously storing the beginning portions of all video programs. Typically, all N video programs are initiated at the same instant. If there is a requirement that the user be able to start watching any program, including when zapping from a program he or she was watching, the buffer has to store data transmitted for N times the staggered time duration, at least if immediate availability is required even in the worst case (request just before a new transmission of the selected program begins, as indicated on Fig.2). Then the buffer size (storable number of Mbytes) C is :

$$C = N \cdot \delta \cdot \beta$$

where N is the number of different video programs,

δ is the staggered time intervals between two successive transmissions of a same program,

β is the bit rate for one program.

[0015] That means that there is a relation between the maximum buffer capacity C_0 assigned to storage of the beginning portions, the staggered time intervals and the number of simultaneous transmissions which are required , conditioned by the number of different video programs and the staggered time interval. For a given capacity C_0 and a

required number N of programs, there should a sufficient number of simultaneous transmission for the staggered time interval δ to be lower than $Co / (N \cdot \beta)$

[0016] The requirements as to the buffer size and / or the required resources are significantly reduced by offsetting the starts of transmissions of a same set of programs by a fraction of the time interval. In a preferred arrangement, illustrated on Fig. 3, the starts of the N programs are evenly distributed inside a period equal to the staggered time interval, i.e. at intervals $\mu = \delta / N$. The transmitted portion of each program which is stored in the buffer is as indicated in crossed lines. It could as well be a same sequence of evenly decreasing storage periods starting from another program.

[0017] In a first embodiment, which permits starting viewing any video program immediately upon request, except from a situation where another program is being watched, a saving ratio close to $[(N - 1) / 2N]$ on the network or satellite link resource may be achieved for a same buffer size, as compared with a situation where transmissions of all programs of a same set start simultaneously. When there is a high number of different transmitted program in the set, the resource saving may approach 50 % in that case.

[0018] Referring to Fig. 3 two successive transmissions of a set of $N = 7$ programs and part of a third transmission are illustrated. Transmissions of the programs begin at intervals of δ / N . Assuming that the maximum buffer size available for program storage is Co , corresponding to a time duration To , then the minimum staggered time δm acceptable between two transmissions of the same program is $\delta m = To / N$.

[0019] When it is necessary or preferable to transmit the whole program for simultaneous access by any user in the arrangement of Fig. 2 and each program has the same duration D, then the number of simultaneously transmitting channels S_{allvp} required for all programs is :

$$\begin{aligned} S_{allvp} &= D / \delta m \cdot N \\ &= D / To \cdot N^2 \end{aligned} \quad (1)$$

[0020] If on the other hand use is made of the approach illustrated in Fig. 3, the the worst case again occurs when there is a request for a video program is just before the beginning of a transmission of that program, as indicated at time t_2 when program 2 is selected. Then the transmitted portion which does not need to be permanently stored in the buffer corresponds to the blank spaces. The time periods which must be stored are then as follows :

Video program 1 : μ
Video program 2 : $N\mu = \delta m$
Video program 3 : 2μ
.....
Video program N : $(N - 1) \mu$

The total duration To to be stored is then :

$To = \mu + 2\mu + 3\mu + 4\mu + \dots + (N - 1) \mu + N\mu = N \cdot (N+1) \cdot \mu / 2$, whatever the program which is selected.

[0021] Such a storing method permits to start watching any of the video program at any time but does not allow to start watching any other program than the selected one once watching has started.

[0022] As a consequence, $\delta m = 2To / (N+1)$

$$\begin{aligned} \text{The number } S_{allvp} &= ND / \delta m \\ &= D / To \cdot N \cdot (N+1) / 2 \end{aligned}$$

[0023] A comparison with (1) shows that the number of simultaneous transmitting channels for all the video programs for a given storage capacity has been reduced by a factor $(N+1)/2N$ compared to the baseline case.

[0024] The reduction is in the ratio $(N-1)/2N$

[0025] Another embodiment (Fig. 4) offers the possibility for starting watching any of the N video program at any time, including during watching a given program; in that case the communications network or satellite link is optimized for saving a percentage of $(N^2 - 3N + 2) / (2N^2)$ of the network resource with respect to the case where no time shift is applied between the transmission starting times of the different video programs. In that case additional storing duration δ for the watched program during watching of the program has to be provided.

[0026] The worst case is when a selected video program is requested at the end of the beginning portion. Then the contiguous slicing process implies to allocate the storing duration δ for the program during the whole watching. The worst case is selection μ seconds after the first program was selected.

[0027] As illustrated on Fig. 4, just before the beginning portion of video program 3 stops (worst case), the periods for which transmission has to be stored are:

Video program 1: 2μ
 Video program 2: δ
 Video program 3: $N\mu$
 Video program 4: $(N-1)\mu$
 ...
 Video program N: 3μ

[0028] Thus the total "duration" that has to be stored on the user buffer device is:

$$T_o = 2\mu + 3\mu + \dots + (N-1)\mu + N\mu + \delta = (\mu = 2\mu + 3\mu + \dots + N\mu) + N\mu - \mu - N(N+1)\mu/2 + N\mu - \mu$$

$$T_o = \mu(N(N+1)/2 + N - 1)$$

[0029] Again the sum is constant whatever the program previously watched and the newly selected program watching any of the video program may be started at any time and watching another program than the firstly selected one is possible once watching has started.

[0030] When fulfilling the necessary conditions:

$$T_o = (N(N+1)/2 + N - 1) \cdot \delta m / N$$

[0031] Hence:

$$\delta m = T_o / ((N+1)/2 + N - 1/N)$$

$$S_{allvp} = N D / \delta m$$

$$= D / t_o \cdot [N(N+1) / 2 + N - 1]$$

[0032] The number of simultaneous transmitting channels for all the video programs has been reduced by a factor $(N(N+1)/2 + N - 1/N^2)$ as compared with formula (1) to the baseline case. This corresponds to a reduction ratio of:

$$(1 - (N(N+1)/2 + N - 1)/N^2) = ((N^2 - 3N + 2)/(2N^2))$$

[0033] The system schematically illustrated in Fig. 5 includes a server 10 connected to an interactive network 12 allowing transfer of data to and from user's terminals 14 via a plurality of channels. Each terminal 14 may be conventional in nature and be a decoder of available type, typically having a view box in compliance with commercial standards as DVD, MPEG 2, MPEG 4, VIDEO CD, MACROVISION. The terminal is connected to or embodied in one or more TV sets 16 and is connected to the network by a bi-directional transmission line 18. It further includes a buffer 20 of sufficient size for fulfilling the above requirements and various conventional components, including a processing unit 22 in which software for determining the end of the beginning period and splicing the video program portions is stored. Such processing unit controls the various steps which have been defined hereinabove.

Claims

1. A method of providing video-on-demand (VOD) comprising the steps of:

- repeatedly transmitting a set comprising a plurality of N video programs at staggered time intervals from a VOD server to a network for access by a view box of an user, and
- responsive to a request for access to a selected one of said programs by said user,

5 selecting that in-progress transmission of the selected program for which a lead-in portion is shortest and storing said program in a buffer associated with the view box as it is transmitted, selecting, in a memory associated with the view box, a previously stored beginning portion of said selected program having a time length sufficient to compensate for that of said time intervals and outputting said beginning portion to said view box for display, and

10 continuously splicing the in-progress transmission stored in the buffer to a conclusion of the beginning portion,

characterized in that all different video programs in a same set are transmitted with time shifts equal to a fraction of the staggered interval.

15 **2.** A process according to claim 1, **characterized in that** all time shifts between two successive transmission are a same fraction $1/N$ of the staggered time interval .

3. A method according to claim 1 or 2, further comprising the step of downloading said beginning portion of a specific said program into all view boxes connected to said server during a last period of low network load prior to availability of said program from the server.



20

4. A video on demand system having :

- at a head end of the network, a server for repeatedly transmitting a set comprising a plurality of N video programs at staggered time intervals (δ) to a network for access by a view box of an user, and
 - at user's ends, a plurality of view boxunits each having a bidirectional connection with said server, each said endbox comprising :
- a buffer for simultaneous writing in of a program transmitted on the network by said server and read out of said program with a time difference between writing in and read out of a same portion,
 - memory means for storing beginning portions of predetermined duration of a plurality of programs adapted to be received and displayed by said view box unit,
 - user operated means for selectively tuning said view box unit for reception of a program repeatedly originating from said server as successive transmissions at time intervals on different channels, and storing that transmission of said program which began most recently as it proceeds,
 - means for reading out the beginning portion of the program which has been selected from the memory means , and
 - switching means for splicing the selected beginning portion with the following portion of the same program for display when said following portion becomes available from the buffer,
- 30
- 35
- 40

characterized in that said server is arranged for transmitting all different video programs in a same set with time shifts equal to a fraction of the staggered interval.

45 **5.** A system according to claim 4, wherein said buffer is part of said memory means.






FIG. 3.




FIG. 4.




FIG. 5.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 40 1679

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	WO 92 11713 A (GTE SERVICE CORP ;GTE LABORATORIES INC (US)) 9 July 1992 (1992-07-09)	1,4	H04N7/173
A	* the whole document *	2,3,5	
Y	--- PATENT ABSTRACTS OF JAPAN vol. 1997, no. 12, 25 December 1997 (1997-12-25) & JP 09 219852 A (SONY CORP), 19 August 1997 (1997-08-19) * abstract *	1,4	
A	--- US 5 793 412 A (ASAMIZUYA NOBORU) 11 August 1998 (1998-08-11) * column 6, line 4 - column 7, line 18 *	1-5	
A	--- WO 96 13125 A (IMEDIA CORP) 2 May 1996 (1996-05-02) * abstract *	1-5	
A	--- EP 0 633 694 A (DIGITAL EQUIPMENT CORP) 11 January 1995 (1995-01-11) * column 12, line 42 - column 14, line 8 *	1-5	
A	--- US 5 884 141 A (SHIMAZU AKIRA ET AL) 16 March 1999 (1999-03-16) * the whole document *	1-5	<div>TECHNICAL FIELDS SEARCHED (Int.Cl.7)</div> <div>H04N</div>
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 9 August 2000	Examiner Greve, M
<div>CATEGORY OF CITED DOCUMENTS</div> <div> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document </div>			

EPO FORM 1503 03/02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 40 1679

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-08-2000

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9211713	A	09-07-1992	CA 2075921 A	22-06-1992
			DE 69126865 D	21-08-1997
			DE 69126865 T	20-11-1997
			EP 0516828 A	09-12-1992
			US 5583937 A	10-12-1996

JP 09219852	A	19-08-1997	NONE	

US 5793412	A	11-08-1998	WO 9608926 A	21-03-1996
			US 5917538 A	29-06-1999

WO 9613125	A	02-05-1996	US 5612742 A	18-03-1997
			AU 3896695 A	15-05-1996
			CA 2202350 A	02-05-1996
			DE 69511570 D	23-09-1999
			DE 69511570 T	17-02-2000
			EP 0787408 A	06-08-1997
			JP 10507889 T	28-07-1998
			US 5926205 A	20-07-1999

EP 0633694	A	11-01-1995	US 5414455 A	09-05-1995
			US 5442390 A	15-08-1995
			CA 2127347 A	08-01-1995
			DE 69415880 D	25-02-1999
			DE 69415880 T	19-08-1999

US 5884141	A	16-03-1999	JP 8079685 A	22-03-1996
			JP 8116515 A	07-05-1996
			CN 1129879 A	28-08-1996
			EP 0700206 A	06-03-1996
			US 5729280 A	17-03-1998
			US 5990881 A	23-11-1999
			US 5826168 A	20-10-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82